


ULTIMO TILE

DRY BACK

GB	HU	RO	SK		ULTIMO TILE
Dimension	Méret	Dimensiuni	Rozmery	EN ISO 24342	32,9 x 65,9 cm
Total thickness	Teljes vastagság	Grosime totală	Celková hrúbka	EN ISO 24346	2,5 mm
Wearlayer thickness	Kopóréteg vastagság	Grosime strat de uzură	Hrubka nášľapnej vrstvy	EN ISO 24340	0,55 mm
European classification	Európai minősítés	Certificare europeană	Európska klasifikácia	EN ISO 10874	23, 33, 42
PUR+ layer	PUR+ réteg	Strat PUR+	Vrstva PUR+		
Total weight	Tömeg	Greutate	Hmotnosť	EN ISO 23997	4.059 gr/m²
Fire class	Éghetőségi besorolás	Categorie de inflamabilitate	Požiarňa trieda	EN 13501	B_{fl}-s1
Residual indentation	Maradandó benyomódás	Deformare permanentă	Statické vtláčanie	EN ISO 24343	≤ 0,10 mm
Static electrical probersity	Elektrosztatikus feltöltődés	Încărcare electrostatică	Elektrostatiký náboj	EN 1815	< 2 kV
Light fastness	Színtartósság	Stabilitatea culorii	Farebná stálosť	ISO 105-B02	≥ 6
Electrical resistance	Elektromos tulajdonság	Caracteristici electrice	Elektrické vlastnosti	EN 1081	≤ 10⁹ Ω
Slip resistance	Csúszási ellenállás	Rezistență la derapaj	Protišmyková ochrana	DIN 51 130	R10
Abrasion group	Kopásállóság	Rezistență la uzură	Odolnosť proti odieraniu	EN 660-2	T
Thermal resistance	Hőátbocsátási ellenállás	Rezistență termică	Tepelný odpor	EN ISO 12664	0,01 m².K/W
Dimensional stability	Méretstabilitás	Stabilitate dimensională	Rozmerová stabilita	EN ISO 23999	≤ 0,25 %
Sound insulation	Hangszigetelés	Izolare fonică	Zvuková izolácia	EN 140-8	4 dB
Curling	Hullámosodás	Formare cute	Vlnenie	EN ISO 23999	≤2mm
Emission of formaldehyde	Formaldehid kibocsátás	Emisie de formaldehidă	Obsah formaldehydu	EN 717-1	E1
Slip resistance	Csúszási ellenállás	Rezistență la derapaj	Protišmyková ochrana	EN 13893	DS
Castor chair test	Görgősszék álló	Rezistent la roțile scaunelor ergonomice	Odolná proti vplyvu kolieskových stoličiek	EN 425	no damage
					nem károsodik
					nu face avarii
					nepoškodzuje sa
Underfloor heating	Padlófűtés	Încălzire prin pardoseală	Podlahové kúrenie	EN 12524	max.27°C
Packaging	Csomagolási egység	Unitate de ambalare	Baliaca jednotka		16 db panel/ 16 buc. panele/ 16 ks panelov = 3,47 m²
Garantee for residential use	Garancia lakossági felhasználás esetén	Garanție pentru uz rezidențial	Záruka pre použitie v obytných priestoroch	year / év / an / rok	20

